



RELTEC® CIRCULAR TEXTURA

DESCRIPTION

SELF-SUPPORTING disposable formwork made up of **high impact polystyrene (HIPS)** and an **external fibreglass reinforcement** to withstand the pressure of the concrete.

USE

 Formwork for reinforced concrete pillars, of circular section, with a textured and visible finish.

RELTEC

TECHNICAL CHARACTERISTICS

Characteristics	Value	
Diameter	From Ø 250 to Ø 600 mm	
Finishing	Textured finish	
Stripping	Pull the supplied cable. No stripping substances are required	
Standard height	4000 mm	
Maximum height of manufacture	4000 mm	
Interior waterproofing	Resistant to concrete moisture	
Tightness	COMPLETELY TIGHT for smooth and visible finishes	

DIAMETER (mm)	WEIGHT (Kg/m)	THICKNESS (mm)
Ø 250	4,16	2,0 ± 0,5
Ø 300	5,20	2,0 ± 0,5
Ø 350	6,30	2,0 ± 0,5
Ø 400	8,88	2,0 ± 0,5
Ø 450	10,79	3,5 ± 0,5
Ø 500	11,98	3,5 ± 0,5
Ø 550	13,18	3,5 ± 0,5
Ø 600	14,37	3,5 ± 0,5



TEXTURE

MOD. 004

Wood texture

Important note:

• For protection, covering with plastic is recommended to prevent the formwork being exposed to sun or rain during storage. Similarly, avoid putting weight on the formwork so as not to cause deformities.